

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 50999970 T329
Print date 16.11.2015 Revision date 29.06.2015
Version 34.0 Issue date 29.06.2015
ENG
Page 1 / 9

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Article No. (manufacturer/supplier): 50999970
Identification of the substance or mixture T329
alle Farbtöne
all colour shades

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

coating material, solvent based, use acc. to technical data sheet

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

Wilckens Farben GmbH
Schmiedestrasse 10 Telephone: +49 4124 606-0
D-25348 Glückstadt Telefax: +49 4124 1537

Dept. responsible for information:

laboratory
E-mail (competent person) lab@wilckens.com

1.4. Emergency telephone number

Emergency telephone number +49 4124 606 188

2. Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing vapours.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P391 Collect spillage.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P501.W1 Content / container disposal in accordance with national official regulations

contains:

Hydrocarbons, C8-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 50999970 T329
Print date 16.11.2015 Revision date 29.06.2015
Version 34.0 Issue date 29.06.2015

ENG
Page 2 / 9

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains 2-ethylhexanoic acid, Zirconiumsalt; 2-butanone oxime. May produce an allergic reaction.

2.3. **Other hazards**

3. Composition / Information on ingredients

3.2. **Mixtures**

Product description / chemical characterization

Description alkyd resin paint

Hazardous ingredients

Classification according to Regulation (EC) No. 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification:	Wt % Remark
215-535-7 1330-20-7 601-022-00-9	01-2119488216-32-XXXX xylene Flam. Liq. 3 H226 / Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Asp. Tox. 1 H304 / STOT RE 2 H373 / STOT SE 3 H335	2,5 < 5
265-185-4 64742-82-1 649-330-00-2	01-2119458049-33-XXXX Naphtha (petroleum), hydrodesulfurized heavy, thermally cracked, low boiling (K21 / K30) benzene content of <0.1% Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / STOT RE 1 H372 / STOT SE 3 H336 / Aquatic Chronic 2 H411	10 < 12,5
928-136-4 64742-82-1	01-2119484809-19-XXXX Hydrocarbons, C8-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / STOT SE 3 H336 / Aquatic Chronic 2 H411	25 < 50
245-018-1 22464-99-9	01-2119979088-21-0000 2-ethylhexanoic acid, Zirconiumsalt Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Repr. 2 H361	< 0,5
202-496-6 96-29-7 616-014-00-0	01-2119539477-28-XXXX 2-butanone oxime Carc. 2 H351 / Acute Tox. 4 H312 / Eye Dam. 1 H318 / Skin Sens. 1 H317	< 0,5

Additional information

Full text of H-phrases: see section 16.

4. First-aid measures

4.1. **Description of first aid measures**

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 50999970 T329
Print date 16.11.2015 Revision date 29.06.2015
Version 34.0 Issue date 29.06.2015

ENG
Page 3 / 9

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Cool closed containers that are near the source of the fire.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 50999970 T329
Print date 16.11.2015 Revision date 29.06.2015
Version 34.0 Issue date 29.06.2015

ENG
Page 4 / 9

Observe technical data sheet. Observe instructions for use.

8. Exposure controls / Personal protection

8.1. Control parameters

Occupational exposure limit values:

xylene, mixture of isomers

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

IOELV, TWA: 221 mg/m³; 50 ppm

IOELV, STEL: 442 mg/m³; 100 ppm

Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha benzenecontent < 0,1% REACH
01-2119458049-33

EC No. 919-446-0

TWA: 100 mg/m³

STEL: 200 mg/m³

Remark: (C9-C15 Aromaten)

Hydrocarbons, C8-12, n-alkanes, isoalkanes, cyclics aromatics (2-25%)

EC No. 928-136-4

TWA: 100 mg/m³

STEL: 200 mg/m³

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state liquid

Colour refer to label

Odour characteristic

Safety relevant basis data

Flash point:

Unit

27 °C

Method

DIN 53213-1

Remark

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 50999970 T329
Print date 16.11.2015 Revision date 29.06.2015
Version 34.0 Issue date 29.06.2015

ENG
Page 5 / 9

(08/2002: replaced
by EN ISO 1523)

Ignition temperature in °C: 200 °C
Lower explosion limit: 0,8 Vol-%
Upper explosion limit: 7,0 Vol-%
Vapour pressure at 20 °C: 2,96 mbar
Density at 20 °C: 1,01 g/cm³
Water solubility (g/L): insoluble
pH at 20 °C: -
Viscosity at 20 °C 200 s 4 mm
Solvent separation test (%) < 3 %
Solid content (%): 51 Wt %
solvent content:
Organic solvents: 48 Wt %
Water: 0 Wt %

TM 33a

9.2. **Other information:**

10. Stability and reactivity

10.1. **Reactivity**

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No data on preparation itself available.

11.1. **Information on toxicological effects**

Acute toxicity

xylene

oral, LD50, Rat: 3523 - 8700 mg/kg

dermal, LD50, Rat:

dermal, LD50, Rabbit: > 2000 mg/kg

Naphtha (petroleum), hydrodesulfurized heavy, thermally cracked, low boiling (K21 / K30) benzene content of <0.1%

oral, LD50, Rat: > 15000 mg/kg

dermal, LD50, Rabbit: > 3500 mg/kg

inhalative (Gases), LC50, Rat: > 14 ppmV (4 h)

2-butanone oxime

oral, LD50, Rat: 2528 mg/kg

dermal, LD50, Rat: > 900 mg/kg

inhalative (Gases), LC50, Rat: 10,5 ppmV (4 h)

phthalic anhydride

oral, LD50, Rat:

skin corrosion/irritation; Serious eye damage/eye irritation

xylene

Skin (4 h)

Eyes

Respiratory or skin sensitisation

Toxicological data are not available.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 50999970 T329
Print date 16.11.2015 Revision date 29.06.2015
Version 34.0 Issue date 29.06.2015

ENG
Page 6 / 9

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

2-ethylhexanoic acid, Zirconiumsalt
Reproductive toxicity

Specific target organ toxicity

xylene

Specific target organ toxicity (single exposure), Irritation:
Specific target organ toxicity (repeated exposure):

Naphtha (petroleum), hydrodesulfurized heavy, thermally cracked, low boiling (K21 / K30) benzene content of <0.1%
Specific target organ toxicity (repeated exposure):

Aspiration hazard

xylene

Aspiration hazard

Naphtha (petroleum), hydrodesulfurized heavy, thermally cracked, low boiling (K21 / K30) benzene content of <0.1%
Aspiration hazard

Hydrocarbons, C8-12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
Aspiration hazard

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No. 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

xylene

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1 - 165 mg/L (48 h)
Algae toxicity, IC50: Algae: (72)

Naphtha (petroleum), hydrodesulfurized heavy, thermally cracked, low boiling (K21 / K30) benzene content of <0.1%
Fish toxicity, LC50, Oncorhynchus mykiss: 10 - 30 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 10 - 22 mg/L (48 h)
Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 4,6 - 10 mg/L (72 h)

2-butanone oxime

Fish toxicity, LC50: > 100 mg/L (96 h)
Daphnia toxicity, EC50: 201 mg/L (48 h)
Algae toxicity, ErC50: 11,8 mg/L

Long-term Ecotoxicity

xylene

Fish toxicity, LC50, Lepomis macrochirus (Bluegill): (96 h)

Naphtha (petroleum), hydrodesulfurized heavy, thermally cracked, low boiling (K21 / K30) benzene content of <0.1%
Fish toxicity, LC50: (96 h)
Daphnia toxicity, EC50: 0 - 22 mg/L (48 h)
Algae toxicity, ErC50: 4,6 - 10 mg/L
Daphnia toxicity, NOEC, Daphnia magna: 0,097 mg/L (21 d)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 50999970 T329
Print date 16.11.2015 Revision date 29.06.2015
Version 34.0 Issue date 29.06.2015

ENG
Page 7 / 9

Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 1 mg/L

12.2. Persistence and degradability

Naphtha (petroleum), hydrodesulfurized heavy, thermally cracked, low boiling (K21 / K30) benzene content of <0.1%
: 74 (28 d)
Readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

13. Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 waste paint and varnish containing organic solvents or other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

1263

14.2. UN proper shipping name

Land transport (ADR/RID): Paint
Sea transport (IMDG): PAINT
Air transport (ICAO-TI / IATA-DGR): Paint

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID) UMWELTGEFAEHRDEND
Marine pollutant p / HYDROCARBONS, LIQUID, N.O.S. aliphatic, low boiling point

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8

Additional information

Land transport (ADR/RID)

tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 50999970
 Print date 16.11.2015
 Version 34.0

T329
 Revision date 29.06.2015
 Issue date 29.06.2015

ENG
 Page 8 / 9

not applicable

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 489
 VOC-value (in g/L) ASTM D-3960-1: 489

according to EU-regulation 2004/42/EC (appendix II)

EU limit value for this product (cat. (Cat. B/e)): 840 g/l (2007)/0 g/l (2010).
 This product contains max 529 g/l VOC.

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
 Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

VSE 4 / VSK 23

15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No. CAS No.	Chemical name	REACH No.
215-535-7 1330-20-7	xylene, mixture of isomers	01-2119488216-32-XXXX
919-446-0	Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha benzenecontent < 0,1% REACH 01-2119458049-33	01-2119458049-33-XXXX
928-136-4	Hydrocarbons, C8-12, n-alkanes, isoalkanes, cyclics aromatics (2-25%)	01-2119484809-19-XXXX

SECTION 16: Other information

Full text of classification in section 3:

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
STOT RE 2 / H373	Specific target organ toxicity (repeated exposure)	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.
STOT RE 1 / H372	Specific target organ toxicity (repeated exposure)	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Skin Sens. 1 / H317	respiratory or skin sensitisation	May cause an allergic skin reaction.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Carc. 2 / H351	Carcinogenicity	Suspected of causing cancer (state route of

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 50999970
Print date 16.11.2015
Version 34.0

T329
Revision date 29.06.2015
Issue date 29.06.2015

ENG
Page 9 / 9

Eye Dam. 1 / H318

Serious eye damage/eye irritation

exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Causes serious eye damage.