

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 52763170  
Print date 16.11.2015  
Version 24.0

TRACTOL 816 1 ltr.  
Revision date 18.08.2015  
Issue date 18.08.2015

ENG  
Page 1 / 9

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifiers

Article No. (manufacturer/supplier): 52763170  
Identification of the substance or mixture TRACTOL 816 1 ltr.  
BS 631 GREY PRIMER  
T816631HE1

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses:

coating material, solvent based, use acc. to technical data sheet

### 1.3. Details of the supplier of the safety data sheet

#### supplier (manufacturer/importer/downstream user/distributor)

Wilckens Farben GmbH

Schmiedestrasse 10

D-25348 Glückstadt

Telephone: +49 4124 606-0

Telefax: +49 4124 1537

#### Dept. responsible for information:

laboratory

E-mail (competent person)

lab@wilckens.com

### 1.4. Emergency telephone number

Emergency telephone number +49 4124 606 188

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Flam. Liq. 3 / H226

flammable liquids

Flammable liquid and vapour.

Skin Irrit. 2 / H315

skin corrosion/irritation

Causes skin irritation.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

STOT SE 3 / H335

Specific target organ toxicity (single exposure)

May cause respiratory irritation.

STOT RE 2 / H373

Specific target organ toxicity (repeated exposure)

May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3 / H412

Hazardous to the aquatic environment

Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Warning

##### Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take precautionary measures against static discharge.

P260 Do not breathe vapour.

P261 Avoid breathing vapours.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) No 453/2010**



Article No.: 52763170  
 Print date 16.11.2015  
 Version 24.0

TRACTOL 816 1 ltr.  
 Revision date 18.08.2015  
 Issue date 18.08.2015

ENG  
 Page 2 / 9

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P314 Get medical advice/attention if you feel unwell.  
 P332 + P313 If skin irritation occurs: Get medical advice/attention.  
 P337 + P313 If eye irritation persists: Get medical advice/attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.  
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P501.W1 Content / container disposal in accordance with national official regulations

**contains:**

xylene

**Supplemental Hazard information (EU)**

EUH208 Contains 2-butanone oxime; Amide Ether. May produce an allergic reaction.

2.3. **Other hazards**

**3. Composition / Information on ingredients**

3.2. **Mixtures**

**Product description / chemical characterization**

**Description** alkyd resin paint

**Hazardous ingredients**

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

EC No. CAS No. INDEX No.	REACH No. Chemical name classification:	Wt % Remark
215-535-7 1330-20-7 601-022-00-9	01-2119488216-32-XXXX xylene Flam. Liq. 3 H226 / Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Asp. Tox. 1 H304 / STOT RE 2 H373 / STOT SE 3 H335	20 < 25
202-849-4 100-41-4 601-023-00-4	01-2119489370-35-XXXX ethylbenzene Flam. Liq. 2 H225 / Acute Tox. 4 H332 / Asp. Tox. 1 H304 / STOT SE 3 H335 / Aquatic Chronic 3 H412	5 < 10
231-944-3 7779-90-0 030-011-00-6	01-2119485044-40-0000 Trizincbis(orthophosphate) Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	< 0,5
202-496-6 96-29-7 616-014-00-0	01-2119539477-28-XXXX 2-butanone oxime Carc. 2 H351 / Acute Tox. 4 H312 / Eye Dam. 1 H318 / Skin Sens. 1 H317	< 0,5
	Amide Ether Skin Sens. 1B H317	< 0,5
	Acrylated Resin Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	< 0,5

**Additional information**

Full text of H-phrases: see section 16.

**4. First-aid measures**

4.1. **Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 52763170  
Print date 16.11.2015  
Version 24.0

TRACTOL 816 1 ltr.  
Revision date 18.08.2015  
Issue date 18.08.2015

ENG  
Page 3 / 9

respiration.

**Following skin contact**

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

**5. Firefighting measures**

5.1. **Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Extinguishing media which must not be used for safety reasons:**

strong water jet

5.2. **Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Cool closed containers that are near the source of the fire.

**6. Accidental release measures**

6.1. **Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

6.4. **Reference to other sections**

Observe protective provisions (see chapter 7 and 8).

**SECTION 7: Handling and storage**

7.1. **Precautions for safe handling**

**Advices on safe handling**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

**Precautions against fire and explosion:**

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. **Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 52763170 TRACTOL 816 1 ltr.  
Print date 16.11.2015 Revision date 18.08.2015  
Version 24.0 Issue date 18.08.2015

ENG  
Page 4 / 9

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

**Hints on joint storage**

Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Further information on storage conditions**

Take care of instructions on label. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. **Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**8. Exposure controls / Personal protection**

8.1. **Control parameters**

**Occupational exposure limit values:**

xylene, mixture of isomers

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

IOELV, TWA: 221 mg/m<sup>3</sup>; 50 ppm

IOELV, STEL: 442 mg/m<sup>3</sup>; 100 ppm

ethylbenzene

INDEX No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

IOELV, TWA: 442 mg/m<sup>3</sup>; 100 ppm

IOELV, STEL: 884 mg/m<sup>3</sup>; 200 ppm

**Additional information**

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

**DNEL:**

Trizincbis(orthophosphate)

INDEX No. 030-011-00-6 / EC No. 231-944-3 / CAS No. 7779-90-0

DNEL long-term dermal (systemic), Workers: 83 mg/kg

DNEL acute inhalative (systemic), Workers: 5 mg/m<sup>3</sup>

DNEL long-term oral (repeated), Consumer: 0,83 mg/kg

DNEL long-term dermal (systemic), Consumer: 83 mg/kg

DNEL long-term inhalative (systemic), Consumer: 2,5 mg/m<sup>3</sup>

**PNEC:**

Trizincbis(orthophosphate)

INDEX No. 030-011-00-6 / EC No. 231-944-3 / CAS No. 7779-90-0

PNEC aquatic, freshwater: 20,6 µg/L

PNEC aquatic, marine water: 6,1 µg/L

PNEC sediment, freshwater: 117,8 mg/kg

PNEC sediment, marine water: 56,5 mg/kg

PNEC, Soil: 35,6 mg/kg

PNEC sewage treatment plant (STP): 100 µg/L

8.2. **Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Occupational exposure controls**

**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Filter Type A2-P3

**Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 52763170  
Print date 16.11.2015  
Version 24.0

TRACTOL 816 1 ltr.  
Revision date 18.08.2015  
Issue date 18.08.2015

ENG  
Page 5 / 9

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.  
Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374  
Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye protection**

Wear closely fitting protective glasses in case of splashes.

**Protective clothing**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

**9. Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**Appearance:**

**Physical state** liquid  
**Colour** refer to label  
**Odour** characteristic

Safety relevant basis data	Unit	Method	Remark
Flash point:	25 °C	DIN 53213-1 (08/2002: replaced by EN ISO 1523)	
Ignition temperature in °C:	500 °C		
Lower explosion limit:	0,8 Vol-%		
Upper explosion limit:	7,0 Vol-%		
Vapour pressure at 20 °C:	3,00 mbar		
Density at 20 °C:	1,39 g/cm <sup>3</sup>		
Water solubility (g/L):	insoluble		
pH at 20 °C:	-		
Viscosity at °C	2000		
Solvent separation test (%)	< 3 %		
Solid content (%):	69 Wt %		
solvent content:			
Organic solvents:	30 Wt %		
Water:	0 Wt %		

**9.2. Other information:**

**10. Stability and reactivity**

**10.1. Reactivity**

**10.2. Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

**10.3. Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

**10.4. Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

**10.5. Incompatible materials**

**10.6. Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No data on preparation itself available.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 52763170 TRACTOL 816 1 ltr.  
Print date 16.11.2015 Revision date 18.08.2015  
Version 24.0 Issue date 18.08.2015

ENG  
Page 6 / 9

**11.1. Information on toxicological effects**

**Acute toxicity**

Trizincbis(orthophosphate)

oral, LD50, Rat: > 5000 mg/kg

xylene

oral, LD50, Rat: 3523 - 8700 mg/kg

dermal, LD50, Rat:

dermal, LD50, Rabbit: > 2000 mg/kg

2-butanone oxime

oral, LD50, Rat: 2528 mg/kg

dermal, LD50, Rat: > 900 mg/kg

inhalative (Gases), LC50, Rat: 10,5 ppmV (4 h)

ethylbenzene

dermal, LD50, Rabbit: 15500 mg/kg

inhalative (vapours), LC50, Rat: 17,2 mg/L (4 h)

**skin corrosion/irritation; Serious eye damage/eye irritation**

xylene

Skin (4 h)

Eyes

**Respiratory or skin sensitisation**

Amide Ether

Skin:

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Toxicological data are not available.

**Specific target organ toxicity**

xylene

Specific target organ toxicity (single exposure), Irritation:

Specific target organ toxicity (repeated exposure):

**Aspiration hazard**

xylene

Aspiration hazard

ethylbenzene

Aspiration hazard

**Practical experience/human evidence**

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

**Remark**

There is no information available on the preparation itself .

**SECTION 12: Ecological information**

**overall evaluation**

Classification according to Regulation (EC) No. 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

**12.1. Toxicity**

xylene



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 52763170 TRACTOL 816 1 ltr.  
Print date 16.11.2015 Revision date 18.08.2015  
Version 24.0 Issue date 18.08.2015

ENG  
Page 7 / 9

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1 - 165 mg/L (48 h)  
Algae toxicity, IC50:, Algae: (72 )

**2-butanone oxime**

Fish toxicity, LC50: > 100 mg/L (96 h)  
Daphnia toxicity, EC50: 201 mg/L (48 h)  
Algae toxicity, ErC50: 11,8 mg/L

**Long-term Ecotoxicity**

**xylene**

Fish toxicity, LC50, Lepomis macrochirus (Bluegill): (96 h)

**12.2. Persistence and degradability**

Toxicological data are not available.

**12.3. Bioaccumulative potential**

Toxicological data are not available.

**Bioconcentration factor (BCF)**

Toxicological data are not available.

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

**13. Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080111 waste paint and varnish containing organic solvents or other dangerous substances

**packaging**

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1. UN number**

1263

**14.2. UN proper shipping name**

Land transport (ADR/RID): Paint  
Sea transport (IMDG): PAINT  
Air transport (ICAO-TI / IATA-DGR): Paint

**14.3. Transport hazard class(es)**

Land transport (ADR/RID): NO GOODS CLASS 3  
in case container size > 450 L class 3  
Sea transport (IMDG) 3  
for packages < 30 litres: Transport in accordance with 2.3.2.5 of the IMDG Code.  
Air transport (ICAO-TI / IATA-DGR) 3

**14.4. Packing group**

III

**14.5. Environmental hazards**

Land transport (ADR/RID) n.a.  
Marine pollutant n.a.

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) No 453/2010**



Article No.: 52763170 TRACTOL 816 1 ltr.  
 Print date 16.11.2015 Revision date 18.08.2015  
 Version 24.0 Issue date 18.08.2015

ENG  
 Page 8 / 9

case of an accident or leakage.  
 Advices on safe handling: see parts 6 - 8

**Additional information**

**Land transport (ADR/RID)**

tunnel restriction code D/E

**Sea transport (IMDG)**

EmS-No. F-E, S-E

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

not applicable

**15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).**

VOC-value (in g/L) ISO 11890-2: 427

VOC-value (in g/L) ASTM D-3960-1: 427

**according to EU-regulation 2004/42/EC (appendix II)**

EU limit value for this product (cat. (Cat. B/c)): 780 g/l (2007)/0 g/l (2010).

This product contains max 427 g/l VOC.

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**Other regulations, restrictions and prohibition regulations**

**15.2. Chemical Safety Assessment**

**For the following substances of this preparation a chemical safety assessment has been carried out:**

EC No.	Chemical name	REACH No.
CAS No.		
215-535-7	xylene, mixture of isomers	01-2119488216-32-XXXX
1330-20-7		

**SECTION 16: Other information**

**Full text of classification in section 3:**

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
STOT RE 2 / H373	Specific target organ toxicity (repeated exposure)	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.
Flam. Liq. 2 / H225	flammable liquids	Highly flammable liquid and vapour.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic life.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.
Carc. 2 / H351	Carcinogenicity	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 52763170  
Print date 16.11.2015  
Version 24.0

TRACTOL 816 1 ltr.  
Revision date 18.08.2015  
Issue date 18.08.2015

ENG  
Page 9 / 9

---

Skin Sens. 1 / H317  
Skin Sens. 1B / H317

respiratory or skin sensitisation  
respiratory or skin sensitisation

May cause an allergic skin reaction.  
May cause an allergic skin reaction.