

Product Information: Select Mini 20W-50

Description

Select Mini 20W-50 is a very high-quality, multigrade mineral lubricant, specially formulated for applications where a combined engine and gearbox configurations utilise a common lubricant. The product is designed to offer exceptional engine protection, whilst ensuring smooth gear shift. Excellent resistance to corrosion and oxidation can be expected as can high shear and thermal stability. The product also exhibits control over foaming and handling of piston deposits, soot and sludge.

Applications

Select Mini 20W-50 is suitable for use in combined engine and gearbox configurations utilise the same lubricant, commonly found in classic mini vehicles from 1959 to 1993 and other combined engine / gearbox vehicles manufactured by Austin, BMC & Leyland.

Performance Features

- Excellent protection against wear
- Protection against corrosion
- Thermally stable
- Enhanced cold flow characteristics
- Excellent foam control
- Resistant to oxidation
- Control over piston deposits, soot and sludge
- High Shear stability
- Promotes smooth gear shifting

Performance Levels

- API SG/CD
- API GL-4

Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.889
Kinematic Viscosity @ 40°C	cSt	145
Kinematic Viscosity @ 100°C	cSt	16.7
Viscosity Index		124
Flashpoint (Open)	°C	210
Pour Point	°C	-36

Figures based on average production values