



Product Information: Agritech 500

Description

Agritech 500 is an SAE 15W-40 super high performance diesel engine oil for normally aspirated and turbocharged diesel engines in tractors and other machinery which make high demands on service intervals and cleanliness. The product incorporates more advanced additive technology than usual tractor engine oils and promotes rapid oil circulation at start-up, reducing wear even at low temperatures. The product also exhibits good engine and piston cleanliness and offers excellent handling of sludge and deposits, the product displays excellent thermal and oxidative stability.

Applications

Agritech 500 is suitable for use as an engine lubricant in Agricultural and off-highway machinery, where the original equipment manufacturer recommends an engine lubricant of this quality, viscosity and performance level.

Performance Features

Protects against sludge and deposits
Good engine and piston cleanliness
Rapid oil circulation at start-up
Thermally stable
Resistance to oxidation

Performance Levels

ACEA E7 (2016)
API CI-4 / SL
Global DHD-1
CAT ECF-1a / ECF-2
Allison C-4
CAT TO-2
Case MS 1121
Cummins CES 20071/2/6/7/8
Deutz DQC III-10
Iveco 18-1804 Classe T2 E7
Mack EO-N
MAN M3275
MB 228.3
MTU DDC Type 2
New Holland 330H
Renault RLD / RLD 2
Steyr A-201
Volvo VDS 3

Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.885
Kinematic Viscosity @ 40°C	cSt	103
Kinematic Viscosity @ 100°C	cSt	14.5
Viscosity Index		145
Flashpoint (Closed)	°C	223
Pour Point	°C	-31

Figures based on average production values