

Product Information

ATF M1375.4

Description

ATF M1375.4 is a synthetic automatic transmission fluid that is specially formulated for use in ZF 6 speed automatic transmissions, used in BMW, Jaguar, Land Rover and Audi vehicles amongst others. This unique formulation offers outstanding wear protection, exceptional thermal and oxidative stability, low temperature performance and shear stability. The high quality base fluid composition and dedicated additive system allow for smooth, trouble free operation even when under the most severe conditions.

Applications

ATF M1375.4 is intended for use in ZF 6 speed automatic transmissions 6HP19; 6HP21; 6HP26; 6HP28 & 6HP32.

Performance Features

- Outstanding frictional performance
- Smooth transmission operation
- Vibration & Shudder free operation
- Excellent anti-wear characteristics
- Thermal, Oxidative & Shear stability
- Excellent low temperature performance

Performance Levels

ZF TE-ML 11

May be used where the following original equipment manufacturer part numbers are specified.

BMW: 8322 0142516

Jaguar: 8432

Land Rover: TYK 500050

Audi/VW: G 055005 A1/A2/A6

Bentley: PY112995PA

Hyundai: 040000C90SG

Aston Martin: 4G4319A509/AA/S

Typical Data

Characteristic	Unit
Density @ 15.6°C	kg/l
Kinematic Viscosity @ 40°C	cSt
Kinematic Viscosity @ 100°C	cSt
Viscosity Index	-
Flash Point (Open)	°C
Pour Point	°C
Colour	-

Method	Result
ASTM D4052	0.875
ASTM D445	29.0
ASTM D445	5.90
ASTM D2270	154
ASTM D92	210
ASTM D97	-51
Visual	Amber