

Product Information: Momentum FSX 5W-30

Description

Momentum FSX 5W-30 is a high quality, fully synthetic passenger car motor oil, manufactured from high quality virgin base stocks and an advanced additive system offering excellent performance in both petrol and diesel engines. The product offers excellent handling of sludge and control of piston deposits, as well as exhibiting high levels of wear protection, oxidation stability, thermal stability, shear stability and protection against rust and corrosion. The product offers outstanding cold flow characteristics at start-up, enabling rapid oil circulation and engine warm-up.

Applications

Momentum FSX 5W-30 is suitable for use in both petrol and diesel fuelled vehicles where the original equipment manufacturer recommends an engine lubricant of this quality, performance level and viscosity.

Performance Features

- Stay in grade performance
- Excellent wear protection
- Protects against rust and corrosion
- Oxidative and thermally stable
- Excellent shear stability
- Control of sludge and piston deposits

Performance Levels

- API SL/CF
- ACEA A5/B5 (2016)
- Ford WSS-M2C913-D(Backward Compatible WSS-M2C913-C)
- Jaguar STJLR 03.5003
- Renault 0700

Typical Data

Characteristic	Unit	Result	Method
Density @ 15.6°C	kg/l	0.857	ASTM D4052
Kinematic Viscosity @ 40°C	cSt	56.0	ASTM D445
Kinematic Viscosity @ 100°C	cSt	9.9	ASTM D445
Viscosity Index		164	ASTM D2270
Flashpoint (Open)	°C	220	ASTM D92
Pour Point	°C	-36	ASTM D97
CCS @ -30°C	mPa•s	4850	ASTM D5293
Total Base Number	mg KOH/g	9.0	ASTM D2896

Figures based on average production values