Valley Street North
Darlington
Co Durham
DL1 1QE

t: 01325 462228
f: 01325 368122
e: enquiries@smithandallan.com
www.smithandallan.com

Momentum FEH 0W-16

Description

Momentum FEH 0W-16 is a high quality, fully synthetic motor oil which has been tailored to meet engine manufacturer specific requirements where a low viscosity engine oil is required. The high-quality synthetic formulation promotes exceptional thermal and oxidation stability, as well as delivering excellent high and low temperature performance. The advanced additive system delivers reduced friction, component protection, enhanced fuel efficiency and protection against LSPI (Low Spark Pre-ignition).

Applications

Momentum FEH 0W-16 has been primarily formulated for use in modern engines where the original equipment manufacturer recommends an engine lubricant of this quality, performance level and viscosity. Manufacturers include Honda, Toyota, Mitsubishi, Nissan and Suzuki.

Performance Features

Reduces friction
Protects against engine wear
Enhanced fuel efficiency
Excellent thermal and oxidation stability
Low evaporation formulation
Exceptional cold flow characteristics
Protection against Low-Speed Pre-Ignition

Performance Levels

API SP+RC
ILSAC GF-6B

Typical Data

Characteristic	Unit	Result	Method
Density @ 15.6°C	kg/l	0.842	ASTM D4052
Kinematic Viscosity @ 40°C	cSt	34.0	ASTM D445
Kinematic Viscosity @ 100°C	cSt	6.75	ASTM D445
Viscosity Index		161	ASTM D2270
Flashpoint (Open)	°C	185	ASTM D92
Pour Point	°C	-39	ASTM D97
CCS @ -35°C	mPa•s	4936	ASTM D5293
Total Base Number	mg KOH/g	7.75	ASTM D2896

Figures based on average production values

Made in the United Kingdom Since 1925

Issue 1 September 2026
The above information is supplied to the best of our knowledge and belief on the basis of current industry and our own development work. Subject to amendment