



Product Information: ATF 3309

Description

ATF 3309 is a high performance automatic transmission fluid, manufactured from high quality synthetic base fluids and formulated for use in certain Aisin-Warner slip-controlled lock-up automatic transmissions.

The fluid offers excellent lubricating characteristics resulting in quiet operation and smooth shifting. Controlled frictional characteristics provide smooth and efficient transmission of power.

Applications

This fluid is intended for use in automatic transmissions where the transmission or vehicle manufacturer recommends a fluid of this quality and performance level.

Performance Features

Smooth shifting and quiet operation
Controlled frictional characteristics
Elimination of transmission shudder
Excellent wear characteristics
Effective protection from rust and corrosion
Excellent resistance to oxidation
Wide temperature service range
Highly resistant to foaming
Compatibility with seal materials

Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.855
Kinematic Viscosity @ 40°C	cSt	36.1
Kinematic Viscosity @ 100°C	cSt	7.4
Viscosity Index		178
Flashpoint (Closed)	°C	206
Pour Point	°C	-45

Figures based on average production values

Performance Levels

JWS-3309

VW Part No: G-055-025-A2

Toyota: ATF T-IV

ATF 3309 is suitable for use in the following vehicle automatic transmissions:

Audi TT, A3 (G-055-025-A2)

Lexus – Most models (JWS 3309/Type T-IV)

Mitsubishi Fuso, FE – 2005 and newer vehicles

Porsche Cayenne S, Cayenne Turbo (JWS 3309/Type-IV)

Saab 9-3, 9-5 & all 5-speed automatics

Toyota – most models (JWS 3309/Type T-IV)

Volkswagen Touareg, Beetle, Cabriolet (G-055-025-A2)

Volvo S60, S70, V70, XC70, C70, S80, XC90, S40, V40 & all 5-speed automatics.