



## Product Information: ATF Dexron II

### Description

A premium automatic transmission fluid formulated using high quality virgin mineral base oils and tailored additives, to meet the performance requirements of GM Dexron IID. The product exhibits consistent frictional performance and provides excellent protection from wear and corrosion. The product is low foaming and displays high frictional stability, allowing for excellent shifting performance.

### Applications

This fluid is intended for use in all application where the equipment manufacturer has requested the use a Dexron IID fluid. Many of these applications include automatic transmissions, power shift transmissions, hydrostatic drives, torque converters, power steering systems and hydraulic systems.

### Performance Features

- Excellent wear and corrosion protection
- Thermally stable
- Resistant to oxidation
- Low foaming
- Consistent frictional performance
- Low temperature performance
- Seal material compatibility

### Performance Levels

- GM: Dexron IID
- Allison: C-4
- Mercedes Benz: 236.2
- Caterpillar: TO-2
- Ford: M2C166-H
- Ford: M2C138-CJ

### Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.863
Kinematic Viscosity @ 40°C	cSt	34.6
Kinematic Viscosity @ 100°C	cSt	7.0
Viscosity Index		169
Flashpoint (Closed)	°C	190
Pour Point	°C	-42

Figures based on average production values