



Product Information: LHM Fluid +

Description

LHM Fluid + is a highly refined mineral based hydraulic brake and levelling fluid. The formulation incorporates anti-wear and lubricity additives as well as displaying excellent cold flow characteristics and very high viscosity index. The fluid also offers high levels of resistance to corrosion and oxidation.

Applications

LHM Fluid + is suitable for use in certain Citroen, Peugeot and Audi vehicles, as well as some agricultural and off-highway applications, where a fluid of this specification and quality is recommended by the original equipment manufacturer.

Performance Features

Excellent levels of wear protection
Protection against corrosion
Excellent cold flow characteristics
Very high viscosity index
Thermal and oxidative stability

Performance Levels

ISO: 7308
PSA: B71 2710
New Holland: NH-610A
Ford: M6C59-A

****Not recommended for use in reservoirs painted black or those using vegetable or synthetic fluids. Not compatible with DOT type brake fluids.**

Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.840
Kinematic Viscosity @ 40°C	cSt	18.1
Kinematic Viscosity @ 100°C	cSt	6.05
Viscosity Index		330
Flashpoint (Closed)	°C	>110
Pour Point	°C	-51°C
Colour		Green

Figures based on average production values