



Product Information: Powertech Pro Comp 2T

Description

Powertech Pro Comp 2T is a high performance synthetic ester based 2 stroke oil, which has been formulated to maintain a tough replenishing layer of protection on critical engine parts, delivering maximum and sustained engine performance even at wide open throttle and high engine speed conditions. The combination of the latest additive technology and high quality synthetic base stocks, provide a lubricant that gives excellent protection against ring sticking and seizure and outstanding engine cleanliness. The product offers excellent resistance to thermal and mechanical breakdown and extremely low levels of exhaust smoke.

Applications

Powertech Pro Comp 2T is recommended for use in oil injection and pre-mix systems used by high output 2 stroke motorcycles, but may also be used in other 2 stroke equipment such as, mopeds, scooters, chainsaws, hedge trimmers, lawnmowers and garden strimmer's where the original equipment manufacturer recommends a lubricant of this quality.

Performance Features

Designed for oil injection & pre-mix use
Extreme protection at maximum rpm
Protection against ring sticking & seizure
Generates a tough heat resistant protection layer
High resistance to thermal & mechanical breakdown
High levels of engine cleanliness
Extremely low levels of exhaust smoke

Performance Levels

JASO FD
ISO-L-EGD
API TC

Always refer to the original equipment manufacturers handbook for suitable mixing ratios and lubricant specification requirement

Typical Data

| Characteristic | Unit | Result |
|-----------------------------|------|--------|
| Density @ 15.6°C | kg/l | 0.881 |
| Kinematic Viscosity @ 40°C | cSt | 61.0 |
| Kinematic Viscosity @ 100°C | cSt | 10.0 |
| Viscosity Index | | 150 |
| Flashpoint (Closed) | °C | 92 |
| Pour Point | °C | -45 |
| Colour | | Red |

Figures based on average production values