GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2022

Revision: 18.08.2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 4 STROKE ENGINE OIL SAE 30
- · Registration number Mixture
- $\cdot$  1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Product category PC24 Lubricants, greases, release products
- · Application of the substance / the mixture Lubricant
- Uses advised against Processes involving extreme heat use advised against.

### $\cdot$ 1.3 Details of the supplier of the safety data sheet

- · Manufacturer/Supplier:
- Smith & Allan Valley Street North Darlington County Durham DL1 1QE Tel: 01325 462228 Fax: 01325 368122 e-mail: enquiries@smithandallan.com
- Further information obtainable from: Product safety department.
- · 1.4 Emergency telephone number:
- UK National Poisons Information Service. E-mail: npis.birmingham@nhs.net; Tel: +44 (0)344 892 0111

# **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements
- H412 Harmful to aquatic life with long lasting effects.
- · Precautionary statements
- P273 Avoid release to the environment.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Additional information:
- EUH208 Contains LOB Calcium long chain alkarylsulphonate, Calcium long chain alkaryl sulphonate. May produce an allergic reaction.
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

# **SECTION 3: Composition/information on ingredients**

### · 3.2 Chemical characterisation: Mixtures

· Description: A blend of highly refined mineral oils with multifunctional additives.

· Dangerous components:		
Polymer	Polyolefin polyamine succinimide	>2.5-≤10%
	Aquatic Chronic 4, H413	
EINECS: 291-829-9	Calcium branched chain alkyl phenate sulphide	≤2.5%
	Aquatic Chronic 4, H413	
	(C	ontd. on page 2)

Printing date 18.08.2022

Revision: 18.08.2022

### Trade name: 4 STROKE ENGINE OIL SAE 30

	(C	Contd. of page 1)
CAS: 68649-42-3	Zinc alkyldithiophosphate	≤2.5%
	🕸 Aquatic Chronic 2, H411; 🕩 Skin Irrit. 2, H315; Eye Irrit. 2, H319	
EINECS: 271-877-7	LOB Calcium long chain alkarylsulphonate	≤2.5%
	🚯 Skin Sens. 1, H317; Aquatic Chronic 4, H413	
	Calcium long chain alkaryl sulphonate	≤2.5%
	🚯 Skin Sens. 1, H317; Aquatic Chronic 4, H413	
	Branched alkylphenol and calcium branched alkyl phenol	≤2.5%
	<ul> <li>Repr. 2, H361;</li> <li>Aquatic Acute 1, H400; Aquatic Chronic 1, H410;</li> <li>Skin Irrit. 2, H315</li> </ul>	
• Additional information: For the wording of the listed hazard phrases refer to section 16.		

**SECTION 4: First aid measures** 

- · 4.1 Description of first aid measures
- · After inhalation: DON'T DELAY!
- After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact: Check for and remove any contact lenses.
- · After swallowing:
- Wash mouth out with water
- If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
- · Information for doctor:

High pressure injection injuries of mineral and synthetic oils through the skin require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture Combustible
- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

# **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Particular danger of slipping on leaked/spilled product. Ensure adequate ventilation
- · 6.2 Environmental precautions:
- Do not allow to penetrate the ground/soil.
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

ater.

(Contd. on page 3) GB

Printing date 18.08.2022

Revision: 18.08.2022

(Contd. of page 2)

## Trade name: 4 STROKE ENGINE OIL SAE 30

### · 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

• 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

• 7.1 Precautions for safe handling No special precautions are necessary if used correctly.

· Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

- Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Store in a bunded area.

• 7.3 Specific end use(s) No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Do not carry product impregnated cleaning cloths in trouser pockets.

Avoid close or long term contact with the skin.

Do not eat, drink, smoke or sniff while working.

Wash hands before breaks and at the end of work.

- Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Goggles recommended during refilling
- · Body protection:

Oil resistant protective clothing

(Contd. on page 4)

Printing date 18.08.2022

Revision: 18.08.2022

(Contd. of page 3)

## Trade name: 4 STROKE ENGINE OIL SAE 30

Body protection must be chosen depending on product properties, activity and possible exposure.

SECTION 9: Physical and chemical properties					
· 9.1 Information on basic physical and chemical properties					
General Information					
· Appearance:					
Form:	Fluid				
Colour: • Odour:	Brown Mineral-oil-like				
· Odour threshold:	Not determined.				
· pH-value:	Not determined.				
-					
<ul> <li>Change in condition Melting point/freezing point:</li> </ul>	Undetermined.				
Initial boiling point and boiling range:					
· Flash point:	>100 °C				
· Flammability (solid, gas):	Not applicable.				
· Ignition temperature:	>250 °C				
· Decomposition temperature:	Not determined.				
· Auto-ignition temperature:	Product is not self-igniting.				
· Explosive properties:	Product does not present an explosion hazard.				
· Explosion limits:					
Lower:	Not determined.				
Upper:	Not determined.				
· Vapour pressure:	Not determined.				
· Density at 20 °C:	0.883 g/cm <sup>3</sup>				
· Relative density	Not determined.				
· Vapour density	Not determined.				
· Evaporation rate	Not determined.				
· Solubility in / Miscibility with					
water:	Not miscible or difficult to mix.				
· Partition coefficient: n-octanol/water:	Not determined.				
· Viscosity:					
Dynamic:	Not determined.				
Kinematic:	Not determined.				
· Solvent content:					
VOC (EC)	0.00 %				
Solids content:	41.8 %				
• 9.2 Other information	No further relevant information available.				

# **SECTION 10: Stability and reactivity**

 $\cdot$  10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 5)

GB

Printing date 18.08.2022

Revision: 18.08.2022

(Contd. of page 4)

### Trade name: 4 STROKE ENGINE OIL SAE 30

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Strong oxidising agents.
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

## **SECTION 11: Toxicological information**

### · 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

### Highly refined mineral oil

01		
Oral		>2,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:

Prolonged and repeated contact with USED engine oils may cause serious skin disorders, including dermatitis and cancer. Engine oils are known to accumulate polycyclic aromatic hydrocarbons in use and there is evidence that used crankcase oils from petrol engines are carcinogenic to animals. Used engine oils fall within the definition of 'carcinogen' contained in reg2(1) of COSHH and thus the Carcinogens ACOP applies. Precautions advised by the Enforcing Authorities include controlling exposure by systems of work, personal protection and personal hygiene.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability Inherently biodegradable
- 12.3 Bioaccumulative potential Product is not expected to bioaccumulate.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Harmful to aquatic organisms

- $\cdot$  12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- $\cdot$  12.6 Other adverse effects No further relevant information available.

(Contd. on page 6)

Printing date 18.08.2022

Revision: 18.08.2022

### Trade name: 4 STROKE ENGINE OIL SAE 30

(Contd. of page 5)

## **SECTION 13: Disposal considerations**

### · 13.1 Waste treatment methods

### · Recommendation

- Recommended Hierarchy of Controls:
- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Contact waste processors for recycling information.

Delivery of waste oil to offically authorised collectors only.

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

### · Uncleaned packaging:

### · Recommendation:

Containers, even those that are "empty," may contain residues that can develop flammable vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

Container remains hazardous when empty. Continue to observe all precuations.

Containers, even those that are "empty," may contain residues that can develop hazardous gases and vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

SECTION 14: Transport information			
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void		
<ul> <li>14.2 UN proper shipping name</li> <li>ADR, ADN, IMDG, IATA</li> </ul>	Void		
· 14.3 Transport hazard class(es)			
· ADR, ADN, IMDG, IATA · Class	Void		
· 14.4 Packing group · ADR, IMDG, IATA	Void		
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No		
· 14.6 Special precautions for user	Not applicable.		
<ul> <li>14.7 Transport in bulk according to Anne Marpol and the IBC Code</li> </ul>	4.7 Transport in bulk according to Annex II ofIarpol and the IBC CodeNot applicable.		
· Transport/Additional information:	Not dangerous according to the above specifications.		
· UN "Model Regulation":	Void		

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

(Contd. on page 7)

GB

Printing date 18.08.2022

Revision: 18.08.2022

**Trade name: 4 STROKE ENGINE OIL SAE 30** 

(Contd. of page 6)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H361 Suspected of damaging fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- · Department issuing SDS: Product safety department.
- · Contact:

## · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Repr. 2: Reproductive toxicity - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4