

Product Information: Momentum SS 10W-40

Description

Momentum SS 10W-40 is a passenger car motor oil, formulated using high quality, synthetic and mineral, virgin base oils, which incorporate an advanced additive system. The product exhibits excellent handling of sludge and control of piston deposits and delivers excellent levels of wear protection and is resistant to oxidation. Furthermore, the product protects against rust and corrosion, has excellent shear stability and is resistant to evaporation loss.

Applications

Momentum SS 10W-40 is suitable for use in petrol and diesel fuelled, high-performance, turbo-charged and naturally aspirated passenger cars, light trucks and vans, where the original equipment manufacturer recommends an engine lubricant of this quality, viscosity and performance level. The product is not suitable for use in conjunction with diesel particulate filters.

Performance Features

- Stay in grade performance
- Excellent wear protection
- Protects against rust and corrosion
- Oxidative and thermally stable
- Low evaporative loss
- Excellent shear stability
- Control of sludge and piston deposits

Performance Levels

- API SN/CF
- ACEA A3/B3, A3/B4
- Mercedes Benz 229.1
- Renault 0700 / 0710
- VW 502.00 / 505.00

Typical Data

Characteristic	Unit	Result	Method
Density @ 15.6°C	kg/l	0.872	ASTM D4052
Kinematic Viscosity @ 40°C	cSt	94.0	ASTM D445
Kinematic Viscosity @ 100°C	cSt	14.1	ASTM D445
Viscosity Index		154	ASTM D2270
Flashpoint (Open)	°C	225	ASTM D92
Pour Point	°C	-36	ASTM D97
CCS @ -25°C	mPa•s	6800	ASTM D5293
Total Base Number	mg KOH/g	10.6	ASTM D2896

Figures based on average production values