

Product Information: Ultra 10W-30

Description

Ultra 10W-30 is a multigrade engine oil, which is manufactured from highly refined mineral base stocks and a tailored additive system ensuring reliable and robust performance in both petrol and diesel engines. The product exhibits excellent anti-wear characteristics and ensures high levels of engine cleanliness through control of soot, sludge and piston deposits. The product offers excellent thermal and oxidative stability, as well as protection against rust and corrosion. The shear stable formulation ensures stay in grade performance.

Applications

Ultra 10W-30 is intended for use in normally aspirated and turbo charged diesel engines and petrol engines in passenger cars, light and heavy commercials, buses, agricultural, plant and construction equipment where the original equipment manufacturer recommends a lubricant of this performance level, quality and viscosity.

Performance Features

- Excellent anti-wear performance
- Control of soot, sludge and piston deposits
- Protects against rust and corrosion
- Thermally stable
- Shear stability
- Resistance to oxidation

Performance Levels

API SJ/CF-4, CF

Typical Data

Characteristic	Unit	Result	Method
Density @ 15.6°C	kg/l	0.884	ASTM D4052
Kinematic Viscosity @ 40°C	cSt	71.1	ASTM D445
Kinematic Viscosity @ 100°C	cSt	10.9	ASTM D445
Viscosity Index		143	ASTM D2270
Flashpoint (Open)	°C	212	ASTM D92
Pour Point	°C	-33	ASTM D97
CCS @ -25°C	mPa•s	7000max	ASTM D5293
Total Base Number	mg KOH/g	9.08	ASTM D2896

Figures based on average production values