SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Trade name: HM Hydraulic ISO 46
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- **Product category** PC17 Hydraulic fluids
- · Application of the substance / the mixture Hydraulic fluid
- · Uses advised against Processes involving extreme heat use advised against.

· 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Smith & Allan Valley Street North Darlington County Durham DL1 1QE Tel: 01325 462228 Fax: 01325 368122 e-mail: enquiries@smithandallan.com

· Further information obtainable from: Product safety department.

· 1.4 Emergency telephone number:

UK National Poisons Information Service. E-mail: npis.birmingham@nhs.net; Tel: +44 (0)344 892 0111

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

- **Classification according to Regulation (EC) No 1272/2008** The substance is not classified, according to the GB CLP regulation.
- The substance is not classified, according to the OD CLI regula
- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · 2.3 Other hazards
- \cdot Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.1 Chemical characterisation: Substances
- · CAS No. Description
- Highly refined mineral oil
- \cdot Identification number(s)
- · Additional information: A blend of highly refined mineral oils with multifunctional additives

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

(Contd. on page 2)

Printing date 01.09.2022

Revision: 24.04.2017

(Contd. of page 1)

Trade name: HM Hydraulic ISO 46

· After eye contact:

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. Then consult a doctor.

- After swallowing:
- Wash mouth out with water

Do not induce vomiting; call for medical help immediately.

If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

· Information for doctor:

High pressure injection injuries of mineral and synthetic oils through the skin require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

• 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Combustible
- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Particular danger of slipping on leaked/spilled product.
- Ensure adequate ventilation
- · 6.2 Environmental precautions:
- Do not allow to penetrate the ground/soil.
- Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

· 6.4 Reference to other sections No dangerous substances are released.

SECTION 7: Handling and storage

\cdot 7.1 Precautions for safe handling

Prevent formation of aerosols.

Ensure good ventilation/exhaustion at the workplace.

• Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

(Contd. on page 3)

Printing date 01.09.2022

Revision: 24.04.2017

Trade name: HM Hydraulic ISO 46

(Contd. of page 2) · Information about storage in one common storage facility: Store away from oxidising agents. • Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Store in a bunded area. • 7.3 Specific end use(s) No further relevant information available. **SECTION 8: Exposure controls/personal protection** · 8.1 Control parameters · Additional information about design of technical facilities: No further data; see item 7. • Ingredients with limit values that require monitoring at the workplace: Not required. · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Personal protective equipment: · General protective and hygienic measures: Do not carry product impregnated cleaning cloths in trouser pockets. Avoid close or long term contact with the skin. Do not eat, drink, smoke or sniff while working. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Do not inhale gases / fumes / aerosols. · Respiratory protection: Not necessary if room is well-ventilated. · Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. · Eye protection: Safety glasses Goggles recommended during refilling · Body protection: Oil resistant protective clothing Body protection must be chosen depending on product properties, activity and possible exposure. SECTION 9: Physical and chemical properties

| General Information | | |
|-------------------------------------|---------------------|--|
| Appearance: | | |
| Form: | Fluid | |
| Colour: | Brown | |
| Odour: | Characteristic | |
| Odour threshold: | Not determined. | |
| pH-value: | Not determined. | |
| Change in condition | | |
| Melting point/freezing point: | Undetermined. | |
| Initial boiling point and boiling r | ange: Undetermined. | |
| Flash point: | Not applicable. | |
| Flammability (solid, gas): | Not applicable. | |

Printing date 01.09.2022

Revision: 24.04.2017

Trade name: HM Hydraulic ISO 46

| | (Contd. of page 3) | |
|---|---|--|
| · Decomposition temperature: | Not determined. | |
| · Auto-ignition temperature: | Not determined. | |
| · Explosive properties: | Product does not present an explosion hazard. | |
| · Explosion limits: | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| · Vapour pressure: | Not determined. | |
| · Density at 20 °C: | 0.873 g/cm ³ | |
| · Relative density | Not determined. | |
| · Vapour density | Not determined. | |
| · Evaporation rate | Not determined. | |
| · Solubility in / Miscibility with | | |
| water: | Not miscible or difficult to mix. | |
| · Partition coefficient: n-octanol/water: | Not determined. | |
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic at 40 °C: | 46.0 cSt | |
| · 9.2 Other information | No further relevant information available. | |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- \cdot 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Strong oxidising agents.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:Highly refined mineral oilOralLD50>2,000 mg/kg (rat)DermalLD50>5,000 mg/kg (rabbit)

Inhalative LC50/4 h >20 mg/l (rat)

• Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- \cdot Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- \cdot Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 5)

Printing date 01.09.2022

Revision: 24.04.2017

(Contd. of page 4)

Trade name: HM Hydraulic ISO 46

· STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability Inherently biodegradable
- 12.3 Bioaccumulative potential Product is not expected to bioaccumulate.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. • 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Delivery of waste oil to offically authorised collectors only.

Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

Container remains hazardous when empty. Continue to observe all precuations.

Containers, even those that are "empty," may contain residues that can develop flammable vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

| 14.1 UN-Number | | |
|---------------------------------|------|--|
| ADR, ADN, IMDG, IATA | Void | |
| 14.2 UN proper shipping name | | |
| ADR, ADN, IMDG, IATA | Void | |
| 14.3 Transport hazard class(es) | | |
| ADR, ADN, IMDG, IATA | | |
| Class | Void | |
| 14.4 Packing group | | |
| ADR, IMDĞ, IATA | Void | |

GB

Printing date 01.09.2022

Revision: 24.04.2017

Trade name: HM Hydraulic ISO 46

| (Contd. of page 5) | |
|---|--|
| Νο | |
| Not applicable. | |
| ex II of | |
| Not applicable. Not dangerous according to the above specifications. | |
| Void | |
| | |

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department.
- · Contact:
- Abbreviations and acronyms:
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative