



Product Information: ATF 2634

Description

ATF 2634 is an automatic transmission fluid, manufactured from high quality synthetic base stocks and a dedicated additive package. The fluid offers exceptional thermal and oxidative stability and measured frictional characteristics ensuring smooth and consistent gear shifting as well as excellent anti-shudder performance. The high quality base fluid exhibits excellent low temperature fluidity and offers long fluid life. ATF 2634 also offers outstanding protection against rust, corrosion and excessive wear.

Applications

ATF 2634 is intended for use in ZF 4HP and 5HP automatic transmissions operated by various vehicles or where an automatic transmission fluid of this performance level and quality is recommended for use by the original equipment manufacturer.

Performance Features

- Smooth and consistent gear shifting
- Excellent anti-shudder performance
- Thermally stable
- High resistance to oxidation
- Good low temperature performance
- Excellent wear protection
- Resistance to rust and corrosion
- Long fluid life

Performance Levels

- BMW: 8322 9407765 / 8322 9407807
- Citroen: Z 000169756
- Jaguar: JLM 20238
- Land Rover: STC 4863
- Peugeot: Z 000169756
- VW / Audi: G 052162 A1 / A2 / A6 (VW TL 52 162)
- ZF No: S671 090 170 (ZF Lifeguard Fluid 5)

Typical Data

Characteristic	Unit	Result
Density @ 15.6°C	kg/l	0.849
Kinematic Viscosity @ 40°C	cSt	35.9
Kinematic Viscosity @ 100°C	cSt	7.4
Viscosity Index		178
Flashpoint (Closed)	°C	196
Pour Point	°C	-46
Colour		Red

Figures based on average production values