

Product Information: Powertech 2T TC-W3

Description

Powertech 2T TC-W3 is a premium quality. Specially formulated, two stroke outboard engine oil. The product is manufactured using a special blend of highly refined mineral oil incorporating a tailored, ashless additive system and is non-toxic to marine life. The product is designed to offer superior protection, reduce spark plug fouling and reduce exhaust port deposits.

Applications

Powertech 2T TC-W3 is suitable for use in the majority of water cooled 2 stroke outboard motors, where a non-toxic lubricant is either stipulated or desired. Always refer to the original equipment manufacturers handbook for correct mixing ratios.

Performance Features

- Non-Toxic to marine life
- Reduces spark plug fouling
- Extends valve life
- Reduces exhaust port deposits
- Dyed blue for easy identification

Performance Levels

- NMMA TC-W3
- API TD

Typical Data

Characteristic	Unit	Result	Method
Density @ 15.6°C	kg/l	0.870	ASTM D4052
Kinematic Viscosity @ 40°C	cSt	55.0	ASTM D445
Kinematic Viscosity @ 100°C	cSt	8.9	ASTM D445
Viscosity Index		140	ASTM D2270
Flashpoint (Open)	°C	70	ASTM D92
Pour Point	°C	-35	ASTM D97
Sulphated Ash	% wt	0.01	IP 163
Colour	-	Blue	Visual

Figures based on average production values