



Product Information: Agritech TU Range

Description

Agritech TU oils are designed for use in a wide variety of modern agricultural equipment. They are manufactured from high quality virgin base stocks and an advanced additive package, the formulation is designed to offer reliable performance in a wide range of farming applications. Available in viscosity grades 10W/30 and 15W/40 to satisfy various manufacturer viscosity requirements.

Applications

These products are suitable for most types of diesel and gasoline agricultural engine and tractor transmission/hydraulic systems. They are also suitable for many other applications including oil immersed brakes, powershift transmissions, power steering systems, hydrostatic transmissions and conventional gear drive systems.

Performance Features

- High anti-wear performance
- Excellent Gear Protection
- Resistant to corrosion
- Elimination of brake chatter
- Low foaming properties
- Smooth hydraulic operation
- Strong resistance to oxidation

Performance Levels

- API: CF-4/SF
- API: GL-4
- Massey Ferguson: M1139/M1144
- John Deere: JDM J27
- Caterpillar: TO-2
- ZF: TE-ML-06B, 06Q, 07B

Typical Data

Characteristic	Unit	10W/30	15W/40
Density @ 15.6°C	kg/l	0.879	0.889
Kinematic Viscosity @ 40°C	cSt	71.1	106
Kinematic Viscosity @ 100°C	cSt	10.8	14.5
Viscosity Index		140	135
Flashpoint (Closed)	°C	200	226
Pour Point	°C	-30	-27

Figures based on average production values