

Product Information: Momentum FSX 10W-60

Description

Momentum FSX 10W-60 is a high quality, fully synthetic motor oil which is intended for use in high performance on road engines. A blend of high-quality synthetic base fluids and a tailored additive system provide exceptional wear performance and offer superb film strength even at elevated operating temperatures. The product exhibits excellent control over sludge and high temperature deposits. The high-quality base fluid composition within the product delivers optimum thermal stability, superior anti-oxidant performance and very low evaporation rates.

Applications

Momentum FSX 10W-60 is recommended for turbo-charged and naturally aspirated high-performance engines, where the original equipment manufacturer recommends a lubricant of this quality, performance level and viscosity.

Performance Features

Exceptional wear performance
Control over sludge and high temperature deposits
Protects from corrosion
Superb film strength at elevated temperatures
Optimum thermal stability
Superior anti-oxidant performance
Very low evaporation rates
Resistance to oil cavitation

Performance Levels

API SN
ACEA A3/B4
BMW M Applications

Typical Data

Characteristic	Unit	Result	Method
Density @ 15.6°C	kg/l	0.857	ASTM D4052
Kinematic Viscosity @ 40°C	cSt	160.1	ASTM D445
Kinematic Viscosity @ 100°C	cSt	24.1	ASTM D445
Viscosity Index		183	ASTM D2270
Flashpoint (Open)	°C	250	ASTM D92
Pour Point	°C	-42	ASTM D97
CCS @-30°C	mPa•s	5200	ASTM D5293
Total Base Number	mg KOH/g	10.7	ASTM D2896

Figures based on average production values