



Smith & Allan  
 Valley Street North  
 Darlington  
 Co Durham  
 DL1 1QE



01325 462228  
 01325 368122  
[enquiries@smithandallan.com](mailto:enquiries@smithandallan.com)  
[www.smithandallan.com](http://www.smithandallan.com)

# Product Information: Autolube Grease

## Description

Autolube grease is a premium quality, semi-fluid, water resistant grease which incorporates highly refined mineral oil and a calcium thickener system. The product displays excellent performance in haulage, off-highway and industrial applications, where the presence of water and humid atmospheres can hinder lubricating performance. The product exhibits excellent corrosion protection and pumpability even at low temperatures.

## Applications

Autolube grease is specifically intended for applications where central lubrication systems are fitted onto heavy goods vehicles for chassis lubrication.

## Performance Features

- Highly resistant to water
- Excellent corrosion protection
- Excellent pumpability
- Low temperature performance
- Red in colour for easy identification

## Typical Data

Characteristic	Result
NLGI Grade	000
Appearance	Semi Fluid Grease
Colour	Red
Worked Penetration	445 - 475
Thickening Agent	Calcium
Drop Point	N/A
Base Oil	Refined Mineral Oil
Copper Corrosion IP112	Pass
Temperature Range	-25°C - +80°C

Figures based on average production values



Issue 1 December 2017

The above information is supplied to the best of our knowledge and belief on the basis of current industry and our own development work. Subject to amendment