

# Product Information: Momentum C2 F 0W-30

## Description

Momentum C2 F 0W-30 is a new generation, fully synthetic motor oil featuring emissions compatible technology, which enables diesel particulate filters to remain clean and maintain engine performance. The low viscosity, low friction formulation is designed to deliver improved fuel economy, whilst maintaining engine cleanliness through efficient handling of sludge and deposits and offering exceptional anti-wear performance. The high-quality base stocks and tailored additive system promote outstanding low temperature performance and exhibit both excellent thermal and oxidative stability, as well as protection from rust and corrosion.

## Applications

Momentum C2 F 0W-30 is primarily intended for use in modern Ford and Jaguar Land Rover vehicles and may also be used where the original equipment manufacturer recommends a lubricant of this quality, performance level and viscosity, such as in certain Toyota, Honda and Kia models.

## Performance Features

- Mid-SAPS emission compatible technology
- Protects against engine wear
- Control over sludge and piston deposits
- Excellent oxidation stability
- Improved fuel economy
- Maintains viscosity
- Protects against rust and corrosion
- Outstanding low temperature performance

## Performance Levels

- ACEA C2 (2016)
- Ford WSS-M2C950-A
- Jaguar Land Rover STJLR.03.5007

## Typical Data

Characteristic	Unit	Result	Method
Density @ 15.6°C	kg/l	0.842	ASTM D4052
Kinematic Viscosity @ 40°C	cSt	44.2	ASTM D445
Kinematic Viscosity @ 100°C	cSt	9.4	ASTM D445
Viscosity Index		204	ASTM D2270
Flashpoint (Open)	°C	206	ASTM D92
Pour Point	°C	-48	ASTM D97
CCS @ -35°C	mPa•s	5650	ASTM D5293
Total Base Number	mg KOH/g	7.7	ASTM D2896

Figures based on average production values