

Product Information: Select Gear Oils

Description

Select Gear Oils are high quality, mineral based lubricants that are formulated without the inclusion of extreme pressure additives. The products exhibit good natural film strength and offer protection against rust and corrosion, enhanced cold flow properties can be expected as can high resistance to oxidation and exceptional control over foaming.

Applications

Select Gear Oils are primarily intended for use in manual gearboxes and axles of Veteran, Edwardian, Vintage and Classic cars, motorcycles and commercial vehicles that contain phosphor-bronze components. Select Gear Oils may also be used where the original equipment manufacturer specifies the use of a non-EP lubricant in applications such as Worm Gear Drives; Oil lubricated bearings; reduction gears/hubs; chains and steering boxes.

Performance Features

- Good natural film strength
- Protects against rust and corrosion
- Highly resistant to oxidation
- Safe for phosphor-bronze components
- Exception foaming control
- Enhanced cold flow properties

Performance Levels

API GL-1

Typical Data

Characteristic	Unit	SAE 90	SAE 140
Density @ 15.6°C	kg/l	0.900	0.901
Kinematic Viscosity @ 40°C	cSt	219	422
Kinematic Viscosity @ 100°C	cSt	18.7	28.8
Viscosity Index		95	95
Flashpoint (Open)	°C	230	240
Pour Point	°C	-15	-10

Figures based on average production values